



TRTLIGHTING
ROAD & TUNNEL SYSTEMS

CHALIS

Light Guide

PowerSet



IP66 Ingress Protection



I Electrical Class



IK10 Bowl | **IK08** Top



-20°C Minimum Ambient



8kg Weight



30°C Maximum Ambient



0.14m² Wind Area



LED Light Source

SPECIFICATION

- LED colour temperature of 3000k
- Colour rendering index > 70
- Projected L80 after 100,000 hours
- Power Factor 0.95 at full load
- High quality pressure die cast aluminium components
- Post top mounting 76mm
- Utilising the latest low glare light guiding technology
- UMSUG codes available for full product range
- Tool-less access
- CLO Available
- Light Grey or Black Finish
- Optional surge protection of 10kV/10kA
- Controls - NEMA 3, 5, 7, Miniature Photocell and Zhaga Book 18 (SR) Socket.
- UV Stabilised Polycarbonate Bowl
- In-built Ventilation (breather) Plug for pressure equalisation
- Part Night Dimming (PND) with manual override option
- DALI compatible for use with CMS
- Supplied Pre-Cabled with Arctic Grade PVC flex

RANGE OVERVIEW

Type	System Power	Road Optics	Area Optics	CCT	Lumen Output	CRI
Chalis SYM LGP	25-47W	✓	✓	3000k	Up to 4749lm	>70
Chalis ASY LGP					Up to 4808lm	>70



All information detailed within this datasheet is accurate at the date of issue.
The information provided is subject to change at our discretion.
If any questions arise or extra information is required, please contact TRT Lighting directly.

Chalis LGP Luminaire Datasheet issue April 2020





TRTLIGHTING
ROAD & TUNNEL SYSTEMS

CHALIS

Light Guide

ELECTRICAL CHARACTERISTICS

	Chalis SYM LGP	Chalis ASY LGP
System Power	25W-47W	
LED CCT	3000k	
LED CRI	>70	
Lumen Output	Up to 4749lm	Up to 4808lm
Lumen Maintenance	Projected L80 after 100,000 hours	
Drive Current	504-960mA	
Driver Output	Constant current output with AM dimming	
Power Factor (Full Load/Half Load)	0.95/0.90	
Operational Voltage	220-240VACrms	
Operating Frequency	50/60Hz	
Inrush Current (Apk/50%-uS)	54A/190uS	
Running Current	0.200A max	
Surge Protection (COM/DIF)	10kV/6kV	
Additional Surge Protection (on request)	10kV/10kA	
Lighting Controls Options	NEMA 3, 5, 7, Miniature Photocell, Zhaga Book 18 (SR) Socket, PND and CMS compatible	
Dimming Protocols	DALI	

MECHANICAL CHARACTERISTICS

Housing Material	High pressure die cast aluminium
Bowl Material	UV stabilised polycarbonate
Lens Material	PMMA
Housing Finish	Chromate free pre treatment Polyester powder coat Light Grey (RAL9006) Black (RAL9005)
Ingress Protection Rating	IP66
Weight	8.0kg
Wind Area	0.14m ²
Impact Resistance Rating	IK10 Bowl/IK08 Top
Mounting Methods	Post Top 76mm

The PowerSet module option allows on site power adjustment providing maximum flexibility both in-situ and for stock holding.

Each module accommodates the selection of any one of the range of powers for the Chalis luminaire.



All information detailed within this datasheet is accurate at the date of issue.
The information provided is subject to change at our discretion.
If any questions arise or extra information is required, please contact TRT Lighting directly.

Chalis LGP Luminaire Datasheet issue April 2020

