



FAB Sheet – I-Range

FEATURES	ADVANTAGES	BENEFITS
High quality extruded aluminium 6063T6 body with die-cast LM6 welded end caps	Strong body Corrosion resistant	Suitable for arduous conditions Longer lasting luminaire
500mm, 700mm and 1300mm lengths	Wide range of options to suit application	Optimised lighting designs reducing costs
LED colour temperatures: 3000K or 4000K (<i>alternatives available</i>)	Range to suit various applications	Optimised lighting
Choice of wattages 67-340W	Wide range of options to suit application	Optimised lighting designs reducing costs
Wide variety of optics; Asymmetric, symmetric and counterbeam	Directional lighting	Enhanced lighting
PMMA lenses	High light transmission Durable material	Clear lighting Longer life
Toughened, flat safety glass cover	Vandal resistant Wipeable surface	Less repair works/costs Easier maintenance
IK08 and IP66 ratings	High impact resistance and ingress protection No dust traps	Longer life Less repair works and costs Easier maintenance
Optional lighting controls	Variable controls	Increased levels of energy savings
Projected LED lifetime L90 after 100,000 hours	Reduces maintenance	Maintenance cost and time savings
Manufactured in UK	Parts required are readily available	Quicker resourcing and assistance
5 year warranty	Risk to the contractor and client is reduced	Peace of mind from the backing of an established manufacturer